

ALL LOADS ARE SUBJECT TO INSPECTION BEFORE DUMPING.

Material must be reasonably clean and suitable for processing through our crushing equipment.

ACCEPTED MATERIAL

- + Clean concrete
- + Clean asphalt
- + Clean solid concrete retaining wall blocks
Must be free of trash, plastic, dirt, and other contamination.
- + Concrete with minor embedded or slightly exposed rebar or wire
- + Minor amounts of dirt, sand, or fines associated with demolition material

IMPORTANT

Minor dirt and slightly exposed rebar or wire are acceptable.
Cinder blocks and hollow masonry can conceal wire, metal, trash, or other contaminants.

NOT ACCEPTED

- ✗ Trash, garbage, or construction debris
- ✗ Vapor barrier plastic, geotextile fabric, silt fence, or other plastics
- ✗ Aluminum, copper, brass, or other metals that cannot be removed by magnet
- ✗ Steel fiber-reinforced concrete or concrete with heavy synthetic fibers
- ✗ Excessive dirt, clay, topsoil, mud, or organic material
- ✗ Cinder blocks (CMU), hollow-core blocks, brick, or other masonry products
- ✗ Painted, contaminated, or hazardous material
- ✗ Concrete with excessive rebar, wire, or metal protruding from the material
- ✗ Mixed loads containing unacceptable material

NOTICE TO CUSTOMERS

UNACCEPTABLE LOADS WILL BE REJECTED

AND LOADED BACK ONTO THE CUSTOMER'S TRUCK.

Grove Stone Recycling Center reserves the right to reject any load that does not meet these requirements.

WHEN IN DOUBT, CALL BEFORE HAULING: (828) 570-5925

Please share these guidelines with drivers, subcontractors, and material suppliers before delivery.